

Carrier Route and Automation

3.5 oz or less	Carrier Route				Automator	
	Entry Point	Saturation	High Density Plus	High Density	Basic	5-Digit Scheme
None	0.111	0.117	0.118	0.210	0.136	0.159
DNDC	0.089	0.095	0.096	0.183	0.112	0.135
DSCF	0.083	0.089	0.090	0.175	0.105	0.128
DDU	-	-	-	-	-	-

Nonautomation

3.5 oz or less	Machinable	
Entry Point	AADC	Mixed AADC
None	0.172	0.185
DNDC	0.148	0.161
DSCF	0.141	-
DDU	-	-

Nonautomation

4 oz or less	Carrier Route				Nonmac	
	Entry Point	Saturation	High Density Plus	High Density	Basic	5-Digit
None	0.136	0.144	0.166	0.213	0.364	0.435
DNDC	0.096	0.104	0.126	0.183	0.340	0.411
DSCF	0.082	0.090	0.112	0.175	0.333	0.404
DDU	-	-	-	-	-	-

More than 4 ounces

None	0.436	0.436	0.436	0.528	0.764	0.764
DNDC	0.275	0.275	0.275	0.408	0.601	0.601
DSCF	0.220	0.220	0.220	0.376	0.553	0.553
DDU	-	-	-	-	-	-
Per Pc	0.027	0.035	0.057	0.081	0.109	0.193

11/17/2017

1
Mixed AADC
0.172
0.148
-
-

hinable	
ADC	Mixed ADC
0.458	0.531
0.434	0.507
0.427	-
-	-

0.764	0.764
0.601	0.601
0.553	-
-	-
0.245	0.277